

GHIBLI S1P

3R182T

CE UNI EN ISO 20345:2012 S1P SRC

Low holed shoe, suede back leather thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Shoe with refracting fabric insert.

Soft and lined tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568


SOLE 3 RUN three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE MEMORY, Three-materials extracomfort insole with soft latex Memory no-stress in the heel zone and in the bending point, resistant to the body pressure. Perspiring, removable, anatomic, absorbing, antistatic and antibacterial.

Size 36-47 Shoe weight Sz 42 gr. 510



MATERIALS



TECHNOLOGIES



OGAV 112-191



ANTISAND

SECTORS



LOGISTICS AND
LIGHT INDUSTRY



WOOD METAL CARPENTRY



COMPONENTS AND AUTOMOTIVE

SOLE



3Run is a line with a **sporty** and youthful character, developed for those who work **indoors** and **outdoors on regular surfaces**.

3Run belongs to the **3D generation**. This shoe therefore has **3 different PU injected layers** with relative densities, each specialized to maximize comfort, anti-slip and foot stability.

Some of these models are also equipped with an **antitorsion** insert to guarantee further support to the foot at every step.

PLUS



MEMORY FOAM

The MEMORY FOAM insole guarantees an excellent comfort thanks to the innovative material of which it is made, which allows it to adapt to the shape of the foot. This, in addition to making walking more pleasant, supports posture, improves the fit of the shoe and distributes the body weight better. Moreover, this stabilizes the foot and reduces the impact with the ground, absorbing shocks and guaranteeing an excellent shock absorber.



3PU PATENT

3D is a revolutionary certified technology that offers the only shoe with three different layers of polyurethane injected. The most external section, with hard mix, offers the maximum resistance for the surface contact and perfect SRC performances. The middle part, with a softer mix, assures comfort when walking. The higher section, next to the upper, guarantees better stability to the foot. Three densities and the combination of three colors are the special characteristics of this new shoes generation.

ANTISLIPPING TEST RESULTS



SRC
ANTI-SLIPPING SOLE

SRA ceramic + NaLS	HEEL >= 0,28 FLAT >= 0,32	0,47 0,47
SRB steel + glycerol	HEEL >= 0,13 FLAT >= 0,18	0,23 0,26