

Manual Slim Pen Cutter

WITH SLICE® CERAMIC BLADE

#10476



ambidextrous



finger friendly®



durable
nylon handle

lanyard hole

two cutting
positions



easy, no-tool
blade change



switch blade orientation
for lefties



slim profile
fits tight spaces

#10404

includes 1 Slice®
ceramic blade



longer-lasting Slice® safety blades



never rust



non-
conductive



non-
magnetic



non-
sparking



chemically
inert



safe up to
1600°C



no sharps
box needed



no oil
coating

Why Slice®?

- Slice patented safety blades are safer than traditional blades
- Slice blades last up to 11.2x longer than steel blades
- fewer blade changes means less downtime and fewer injuries
- Slice blades never rust, do not conduct electricity, are non-sparking, and are non-magnetic
- Slice blades are oil and lubricant free
- safer finger-friendly® edge cuts materials effectively
- blades are 100 percent recyclable

Specifications

SKU#	10476
INNER/MASTER	12/192
PACKAGED UNIT	8-95142-10476-7 214 x 83 x 12.95 mm (30 g) 8.43 x 3.27 x 0.51 in (1.06 oz)
INNER	2-08-95142-10476-1
MASTER	5-08-95142-10476-2 45.8 x 40.6 x 20 cm (7.7 kg) 18.03 x 15.98 x 7.87 in (16.98 lb)

Technical

HANDLE MATERIALS	GFN, POM, ABS, Stainless Steel
HANDLE SIZE	139 x 21.7 x 12.15 mm (21.2 g) 5.47 x 0.85 x 0.48 in (0.75 oz)
BLADE MATERIAL	zirconium oxide
CUTTING DEPTH	12 mm (0.47 in) - varies by blade
BLADE SIZE	33.3 x 6.26 x 1.33 mm (1 g) 1.31 x 0.25 x 0.05 in (0.04 oz)

Compatibility

Slice® slim pen cutters are designed to work exclusively with Slice safety blades for optimal safety and function.

#10404

#10408

Contact Us

Slice, Inc. (USA)
38 N. Almaden Blvd Unit 115
San Jose, California 95110 USA
T 408.370.6050 F 408.645.7045
E orders@sliceproducts.com
W www.sliceproducts.com



a portion of purchase
price is donated to
autism research.

© 2020 Slice, Inc.
Slice® is a registered trademark.
Protected by U.S. and foreign patents and patents pending.
Prices, features, specifications subject to change without notice.

SELL10476-20200819

slice®